

Pneumatic atomizing nozzles, wide flat fan, pressure principle, internal mixing Series 136.4

Features:




- Fine flat fan atomization
- Pressure principle
- Internal mixing

Applications:

- Humidification of goods
- Cooling
- Belt humidification




Series 136.4



Liquid connection G ₁	Air connection G ₂	Screw plug thread (size 11)	Weight [lb] (Stainless steel 303)
1/4 NPT	1/4 NPT	5/16-24 UNF-2A	0.5

Spray angle	Ordering number			Narrowest free cross section Ø [in]	Liquid pressure p [psi]												Spray dimensions			
	Type	Material number																		
		1Y	16		10				20				40				60			
		Stainless steel 316L	Stainless steel 303		p air [psi]	v̇ water [gal/h]	v̇ ₁ air [SCFM]	p air [psi]	v̇ water [gal/h]	v̇ ₁ air [SCFM]	p air [psi]	v̇ water [gal/h]	v̇ ₁ air [SCFM]	p air [psi]	v̇ water [gal/h]	v̇ ₁ air [SCFM]	p air [psi]	p water [psi]	B ₁ [in]	B ₂ [in]
45°	136.414.xx.B2	●	●	0.03	15	2.0	0.8	20	3.8	0.9	32	5.9	1.2	44	6.6	1.5	20	10	3	5
					17	1.6	0.9	23	3.4	0.9	38	5.3	1.4	49	6.1	1.6	35	22	4	6
					20	1.1	1.0	26	3.1	1.1	44	4.7	1.5	55	5.5	1.8	46	29	4	6
					23	0.7	1.1	29	2.7	1.2	49	4.1	1.8	61	5.0	2.1	55	44	5	7
					26	0.3	1.2	32	2.4	1.3	55	3.5	2.0	67	4.5	2.2	67	58	5	8
					–	–	–	35	2.0	1.4	61	2.9	2.2	73	3.9	2.5	–	–	–	–
					–	–	–	38	1.6	1.5	67	2.3	2.4	78	3.4	2.7	–	–	–	–
					–	–	–	41	1.2	1.6	73	1.7	2.6	84	2.9	2.9	–	–	–	–
					–	–	–	44	0.8	1.8	78	1.1	2.9	87	2.6	3.1	–	–	–	–
					–	–	–	46	0.6	1.9	84	0.7	3.1	–	–	–	–	–	–	–
					–	–	–	49	0.3	2.0	87	0.4	3.2	–	–	–	–	–	–	–
	136.443.xx.B2	●	●	0.04	17	3.7	0.9	23	7.0	0.9	44	9.8	1.5	52	12.0	1.7	17	10	4	6
					20	3.1	1.0	26	6.4	1.1	49	8.7	1.8	58	11.1	1.9	29	22	5	7
					23	2.5	1.1	29	5.8	1.2	55	7.8	2.0	64	10.1	2.2	41	29	6	7
					26	2.1	1.2	32	5.3	1.3	61	6.9	2.2	70	9.2	2.4	55	44	6	8
					–	–	–	35	4.8	1.4	67	6.1	2.5	75	8.4	2.6	70	58	6	9
					–	–	–	38	4.3	1.5	73	5.3	2.7	81	7.7	2.9	–	–	–	–
					–	–	–	41	3.8	1.6	78	4.6	2.9	87	6.9	3.1	–	–	–	–
					–	–	–	44	3.4	1.8	84	3.9	3.1	–	–	–	–	–	–	–
					–	–	–	46	3.0	1.9	87	3.7	3.2	–	–	–	–	–	–	–
					–	–	–	49	2.6	2.0	–	–	–	–	–	–	–	–	–	–
					–	–	–	52	2.3	3.6	–	–	–	–	–	–	–	–	–	–





Spray angle	Ordering number			Narrowest free cross section Ø [in]	Liquid pressure p [psi]												Spray dimensions			
	Type	Material number																		
		1Y	16		10				20				40				60			
		Stainless steel 316L	Stainless steel 303		p air [psi]	V̇ water [gal/h]	V̇ _{air} [SCFM]	p air [psi]	V̇ water [gal/h]	V̇ _{air} [SCFM]	p air [psi]	V̇ water [gal/h]	V̇ _{air} [SCFM]	p air [psi]	V̇ water [gal/h]	V̇ _{air} [SCFM]	p air [psi]	p water [psi]	B ₁ [in]	B ₂ [in]
45°	136.462.xx.B2	●	●	0.06	17	5.0	1.5	29	5.8	1.2	44	16.3	2.4	55	20.1	2.7	17	10	5	6
					23	3.2	2.0	35	4.8	1.4	49	13.7	2.8	58	18.6	3.0	35	22	5	7
					29	2.5	2.4	41	3.8	1.6	55	11.8	3.4	61	17.3	3.2	46	29	5	7
					35	1.9	2.8	46	3.0	1.9	61	10.3	3.9	64	16.2	3.5	55	44	6	8
					41	1.5	3.2	52	2.3	2.1	67	8.8	4.4	67	15.1	3.8	87	58	6	8
					46	1.3	3.5	58	2.1	2.3	73	7.8	4.8	70	14.3	3.9	–	–	–	–
					52	1.0	3.9	64	1.64	2.5	78	6.74	5.2	73	13.6	4.2	–	–	–	–
					58	0.8	4.2	70	1.2	2.7	84	5.8	5.7	75	13.0	4.5	–	–	–	–
					64	0.6	4.6	75	0.8	2.9	87	5.4	5.8	78	12.3	4.8	–	–	–	–
					–	–	–	81	0.4	3.1	–	–	–	81	11.5	5.1	–	–	–	–
					–	–	–	84	0.2	3.2	–	–	–	84	10.9	5.2	–	–	–	–
					–	–	–	–	–	–	–	–	–	87	10.3	5.5	–	–	–	–
60°	136.425.xx.B2	●	●	0.02	12	1.7	0.7	20	2.5	1.0	35	3.5	1.5	35	4.3	1.5	17	10	6	8
					17	1.5	0.9	26	2.3	1.2	38	3.4	1.6	41	4.1	1.7	32	22	6	10
					23	1.2	1.1	32	2.1	1.4	44	3.2	1.8	46	4.0	1.9	44	29	7	10
					29	1.1	1.4	38	1.9	1.6	49	3.1	2.0	52	3.8	2.1	49	44	8	13
					35	0.8	1.5	44	1.7	1.8	55	2.9	2.2	58	3.7	2.2	81	58	8	13
					41	0.7	1.7	49	1.5	2.0	61	2.7	2.4	64	3.5	2.4	–	–	–	–
					44	0.6	1.8	55	1.3	2.2	67	2.6	2.5	70	3.4	2.6	–	–	–	–
					–	–	–	58	1.3	2.3	73	2.4	2.7	75	3.2	2.8	–	–	–	–
					–	–	–	64	1.1	2.5	78	2.3	2.9	81	3.1	3.0	–	–	–	–
					–	–	–	70	1.0	2.6	84	2.1	3.1	87	3.0	3.2	–	–	–	–
					–	–	–	75	0.7	2.8	87	2.1	3.2	–	–	–	–	–	–	–
					–	–	–	81	0.6	3.0	–	–	–	–	–	–	–	–	–	–
	–	–	–	87	0.4	3.2	–	–	–	–	–	–	–	–	–	–				
	136.452.xx.B2	●	●	0.06	15	5.0	2.3	26	8.2	3.1	46	13.2	4.5	55	18.7	4.8	15	10	5	7
					20	2.3	3.4	29	6.7	3.7	52	10.4	5.5	61	15.5	5.7	26	22	6	9
					26	2.0	4.1	32	5.3	4.2	58	8.3	6.6	67	12.8	6.6	38	29	6	10
					32	1.1	4.9	35	4.1	4.7	64	6.3	7.6	73	10.9	7.7	52	44	7	11
					38	0.3	5.8	38	3.3	5.2	70	4.7	8.5	78	8.9	8.7	73	58	7	11
					41	0.03	6.1	41	2.7	5.7	75	3.5	9.4	84	7.3	9.7	–	–	–	–
					–	–	–	–	–	–	81	2.8	10.3	87	6.4	10.1	–	–	–	–
					–	–	–	–	–	–	87	2.3	11.1	–	–	–	–	–	–	–
80°					136.433.xx.B2	●	●	0.02	15	3.1	1.2	26	4.8	1.6	44	8.2	2.2	55	9.9	2.6
	17	2.1	1.4	29					4.0	1.9	49	6.7	2.6	61	8.6	2.9	32	22	7	10
	20	1.4	1.6	32					3.2	2.1	55	5.4	3.0	67	7.3	3.4	44	29	8	12
	23	1.0	1.9	35					2.6	2.4	61	4.3	3.5	73	6.2	3.8	55	58	12	19
	–	–	–	38					2.0	2.5	67	3.3	3.9	78	5.1	4.2	75	58	10	16
	–	–	–	41					1.6	2.8	73	2.5	4.3	84	4.2	4.6	–	–	–	–
	–	–	–	44					1.2	2.9	78	1.7	4.7	87	3.8	4.9	–	–	–	–
	–	–	–	–					–	–	–	–	–	–	–	–	–	–	–	–

Ordering Type + Material no. = Ordering no.
example: 136.462.xx.B2 + 1Y = 136.462.1Y.B2