


Rotating cleaning nozzle PicoWhirly Series 500.234



Features:

- Cleaning with rotating solid jet
- Compact design for confined spaces
- Suitable for very high temperatures
- Full stainless steel design



Series 500.234

Max. tank diameter [ft]	0	5	10	15	20	25	30
-------------------------	---	---	----	----	----	----	----

Technical data:



Maximum operating temperature
392 °F



Maximum ambient temperature
392 °F



Installation
Operation in every installation position



Bearing
Kolsterised slide bearing



Material
Stainless steel 1.4404 (316L)



Weight
.03 lbs



Surface quality
Ra ≤ 1.6 µm
OUTSIDE



Surface quality
Ra ≤ 1.6 µm
INSIDE



Steam suitability
Suitable



Insertion diameter
.35 in



Recommended filter
Line strainer with a mesh size of 0.3 mm/50 mesh




Recommended operating pressure
45 psi

Function video

www.lechler.com/picowhirly

Or scan the QR code.



Spray angle	Ordering number		Narrowest free cross section Ø [in]	V̇ water [gal/min]							Max. tank diameter [ft]
	Type	Connection		p [psi] (p _{max} = 75 psi)							
		1/8" Male NPT		20	30	40	45	Liters per min. 3 bar	60	75	
300° 	500.234.G9	BA	0.07	1.75	2.15	2.48	2.63	9.8	3.04	3.40	3

The maximum tank diameter applies to the recommended operating pressure and is meant as a recommendation only.
The cleaning result is also affected by the type of soiling.

Compressed air should be used for dry blowing for a short time only. Operation above the recommended operating pressure has a negative impact on the cleaning result and wear.

Also available with an M6 metric connection